



Danfoss A/S

DK-6430 Nordborg
Denmark
CVR nr.: 20 16 57 15

Telephone: +45 7488 2222
Fax: +45 7449 0949

EU DECLARATION OF CONFORMITY

Danfoss A/S
Danfoss Drives

declares under our sole responsibility that the product **VLT Midi Drive FC 280**

Typecodes:

FC-280PXXXYY***ZZ*****

Where:

Character XXX: K37, K55, K75, 1K1, 1K5, 2K2, 3K0, 4K0, 5K5, 7K5, 11K, 15K, 18K, 22K

Character YY: S2, T2, T4

Character ZZ: H1, H2

* may be any number or letter indicating drive options which do not impact this DoC.

Covered by this declaration is in conformity with the following directive(s), standard(s) or other normative document(s), provided that the product is used in accordance with our instructions.

Low Voltage Directive 2014/35/EU

EN61800-5-1:2007

Adjustable speed electrical power drive systems – Part 5-1: Safety requirements – Electrical, thermal and energy.

EMC Directive 2014/30/EU

EN61800-3:2004 + A1:2012

Adjustable speed electrical power drive systems – Part 3: EMC requirements and specific test methods.

Machinery Directive 2006/42/EC

EN61800-5-2:2007

Adjustable speed electrical power drive systems – Part 5-2: Safety requirements - Functional.

Date: 1/7 2016	Issued by Signature: Name: Leo Birkkjær Lauritsen Title: Head of Connectivity, UI and 3 rd Party products	Date: 4/7-16	Approved by Signature: Name: Michael Termansen Title: VP, Design Center DK and DE
----------------------	---	-----------------	--

Danfoss only vouches for the correctness of the English version of this declaration. In the event of the declaration being translated into any other language, the translator concerned shall be liable for the correctness of the translation.

EN62061:2012	Safety of machinery – Functional safety of safety-related electrical, electronic and programmable electronic control systems.
EN61508 Parts 1-7:2010	Functional safety of electrical/electronic/programmable electronic safety related systems.
EN ISO 13849-1:2015	Safety of machinery – Safety-related parts of control systems. Part 1: General principles for design.

The meaning of the 30 characters in the type code string can be found in appendix 00729776.